

DTH HAMMER PMK GIII

PMK 600

APPLICATIONS

- WATER WELL
- SHALLOW OIL & GAS
- CONSTRUCTION
- EXPLORATION

A new generation of DTH hammers.

Why buy a OCMA DRILLTECH HAMMER?

Advantage:

Leader for performance in its class.

The PMK 600 is the best solution for drilling contractors and owner-operators seeking maximum productivity and the most fastest DTH hammer in the world.

Heavy duty hammer with 145 mm diameter outer for extended service life in abrasive conditions and is also suitable for water well drilling.

Superior Designs, built for drilling 165 mm - 216 mm (6 1/2" - 8 1/2") dia. holes and operates at an optimum air pressure between 10.5 - 24 bar (150 - 350 psi).

The PMK 600 hammer is designed to accept Button Bits with a shank Ingersoll Rand DHD 360 and can also be supplied to accept the Mission SD6 and Ingersoll Rand QL60 type of Button Bits.

DTH HAMMER PMK (500

AIR CONSUMPTION

16


PMK 600



HAMMER SPECIFICATIONS

WEIGHT	106 Kg	PSI	BAR	CFM	M³/min
LENGTH	1252 mm	150	10,3	329	9,31
OUTSIDE DIAM. CYLINDER	145 mm	200	13,8	509	14,4
MAX WORKING PRESSURE	24 BAR	250	17,2	707	20,0
THREAD	3" 1/2 API REG	300	20,7	930	26,3
		350	24,0	1041	29,5

BIT SHANK - MISSION SD6 - I.R. QL 60/DHD 360



DESCRIPTION	PART N°
BACKHEAD	OC-01-06
CHECK VALVE	OC-02-06
VALVE SPRING	OC-03-06
AIR DISTRIBUTOR	OC-04-06
SPRING B.	OC-05-06
CONTROL TUBE	OC-06-06
RETAINING RING	OC-07-06
PISTON	OC-08-06
RETAINING RING	OC-09-06
GUIDE BUSH Not for SD6 shank	OC-10-06
BIT RETAINING RING	OC-11-06
СНИСК	OC-12-06
O-RING	OC-13-06
O-RING	OC-14-06
O-RING	OC-15-06
CYLINDER	OC-16-06
	BACKHEAD CHECK VALVE VALVE SPRING AIR DISTRIBUTOR SPRING B. CONTROL TUBE RETAINING RING PISTON RETAINING RING GUIDE BUSH Not for SD6 shank BIT RETAINING RING CHUCK O-RING O-RING

OCMA s.r.l. - Zona Artigianale P.I.P. Lotto D/8 70056 Molfetta (BA) - ITALY DRILLTECH Tel. +39.080.395.50.30 | Fax +39.080.395.14.98

