

# DTH HAMMER PMK

## **PMK 800**

# **APPLICATIONS**

- WATER WELL
- WATER WELL CASING
- SHALLOW OIL & GAS
- -CONSTRUCTION
- -EXPLORATION
- -BLASTHOLE

A new generation of DTH hammers.

Why buy a OCMA DRILLTECH HAMMER?

### Advantage:

A hight performance DTH hammer for all rock conditions and used in almost any drilling applications is suitable for a wide range of air pressures, 7 - 24 bar (100 - 350 psi) Superior Designs, built for drilling 203 mm - 254 mm (8" - 10") dia. holes the PMK 800 is designed to accept Button Bits with a shank Mission SD8.



**15** 


PMK 800



# HAMMER SPECIFICATIONS

WEIGHT	170 Kg	PSI	BAR	CFM	M³/min
LENGTH WITHOUT BIT	1222 mm	150	10,3	500	14,3
OUTSIDE DIAM. CYLINDER	175 mm	200	13,8	660	19,0
REVERSE CYLINDER	•	250	17,2	890	24,9
MAX WORKING PRESSURE	24 Bar	300	20,7	1050	33,0
THREAD	4" 1/2 API REG.	350	24.0	1400	39.0

# **BIT SHANK - MISSION SD8**



ITEM	DESCRIPTION	PART N°
1	BACKHEAD	OC-01-08
2	O-RING	OC-02-08
3	CHECK VALVE	OC-03-08
4	VALVE SPRING	OC-04-08
5	AIR DISTRIBUTOR	OC-05-08
6	SPRING B.	OC-06-08
7	CONTROL TUBE	OC-07-08
8	O-RING	OC-08-08
9	RETAINING RING	OC-09-08
10	PISTON	OC-10-08
11	RETAINING RING	OC-11-08
12	BIT RETAINING RING	OC-12-08
13	O-RING	OC-13-08
14	СНИСК	OC-14-08
15	CYLINDER	OC-15-08

OCMA s.r.l. - Zona Artigianale P.I.P. Lotto D/8 70056 Molfetta (BA) - ITALY DRILLTECH Tel. +39.080.395.50.30 | Fax +39.080.395.14.98

AIR CONSUMPTION

RINA ISO 9001:2000